

EXCEPTIONAL 3D 24" HD GLASSES-FREE 3D DISPLAY

Maximize your messaging without having to maximize your budget.

Exceptional 3D bring's patented glasses-free 3D visualization to a wide range of users by delivering sophisticated, intelligent and complete 3D system solutions. The Exceptional 3D **EX3D-24** is a cost-conscious solution for your glasses-free 3D digital signage applications. The high-performance panel and abundance of advanced technologies promote extended use, while an adaptable mechanical design make these 3D displays ideal for a wide variety of environments. Drive foot traffic and sales in retail stores. Whet appetites in restaurants. Build brand awareness and turn heads during presentations in corporate lobbies and conference rooms. With Exceptional 3D display solutions, you can create dynamic 3D digital signage in any space and achieve your business goals.

24" EXCEPTIONAL 3D: EX3D-24

HD GLASSES-FREE 3D LCD DISPLAY SPECIFICATIONS

| Optimal Viewing Distance 3' - 6' | |
|---|--|
| S0° / 50° | |
| Number of Views 9 | |
| Description Converted Video Formats 1920 x 1080 Tou Tou | |
| Panel Technology TN Viewable Image Size 23" Native Resolution 1920 x 1080 Brightness 250 nits Contrast Ratio (Typical) 1,000:1 Viewing Angle 170° / 160° Response Time (G-to-G) 5ms Aspect Ratio 16:9 Orientation Landscape Displayable Colors More than 16.7 million CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Viewable Image Size 23" Native Resolution 1920 x 1080 Brightness 250 nits Contrast Ratio (Typical) 1,000:1 Viewing Angle 170° / 160° Response Time (G-to-G) 5ms Aspect Ratio 16:9 Orientation Landscape Displayable Colors More than 16.7 million CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Native Resolution 1920 x 1080 Brightness 250 nits Contrast Ratio (Typical) 1,000:1 Viewing Angle 170° / 160° Response Time (G-to-G) 5ms Aspect Ratio 16:9 Orientation Landscape Displayable Colors More than 16.7 million CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Brightness 250 nits 1,000:1 1,000:1 Viewing Angle 170° / 160° Sms Sms Sms Sms | |
| Contrast Ratio (Typical) 1,000:1 Viewing Angle 170° / 160° Response Time (G-to-G) 5ms Aspect Ratio 16:9 Orientation Landscape Displayable Colors More than 16.7 million CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Viewing Angle 170° / 160° Response Time (G-to-G) 5ms Aspect Ratio 16:9 Orientation Landscape Displayable Colors More than 16.7 million CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Response Time (G-to-G) 5ms Aspect Ratio 16:9 Orientation Landscape Displayable Colors More than 16.7 million CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Aspect Ratio 16:9 Orientation Landscape Displayable Colors More than 16.7 million CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Orientation Landscape Displayable Colors More than 16.7 million CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Displayable Colors More than 16.7 million CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| CONNECTIVITY Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Supported Video Formats 1920 X 1080, 1680 X 1050, 1440 X 900, 1280 X 1024, 1280 X 720, 1024 X 768, 800 X 600, 720 X 400, 640 X 480 Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| Input Terminals VGA, DVI-D (with HDCP), HDMI (with HDCP) | |
| | |
| | |
| POWER CONSUMPTION | |
| On (Typical) 33W | |
| ECO Mode Standyby <.06W | |
| PHYSICAL SPECIFICATIONS | |
| Unpackaged Dimensions 16.40"(h) x 21.97"(w) x 6.26"(d) | |
| Packaged Dimensions 15.63"(h) x 23.03"(w) x 4.96"(d) | |
| Unpackaged Weight 8.62 lbs. | |
| Packaged Weight 13.03 lbs. | |
| OTHER | |
| Tilt Yes (0 to +25 degrees) | |
| Certifications ENERGY STAR® qualified, EPEAT® Silver registered | |