

MicroView™ MV35T



See-through heads up display performance in a compact personal viewer.

KEY APPLICATIONS

- Remote viewing of any NTSC/RS170 or RGB device including various video sights, computers, maps, GPS and other data information

KEY FEATURES

- The advanced see-through prism optic provides a wide field of view picture with minimal vision obstruction
- Military eyewear or helmet mounting options
- HMD weighs less than 50 grams
- Left and right eye compatible
- Includes proprietary OLED calibration process

*Now available: lower weight,
lower cost, composite versions*

**Rockwell
Collins**

Building trust every day

DISPLAY MODULE PERFORMANCE PARAMETERS

Image source type	Monochrome Green XL AMOLED 800 (x3) pixels x 600 lines
Resolution	2.1 arcmin/color group
Luminance	0.1-35 foot - Lamberts
Contrast	>100:1
Mechanical weight	Left or right eye compatible standard; clip on to military approved eyewear*
Weight	50 grams
Interface	Includes 1.2 m cable with water- resistant quick disconnect Glenair® connector*
Field of view	SVGA resolution (800 x 600) 28° horizontal x 21° vertical (35° diagonal) NTSC/VGA resolution (640 x 480) 22° horizontal x 17° vertical (28° diagonal)
Optics	Plastic aspheric lens
Exit pupil	Non-pupil forming

*Customized HMD mounting available - call for further information.

*Other cable lengths available - call for further information.

BATTERY OPERATED DISPLAY CONTROL MODULE

Mechanical	Clip on to belt or webbing
Weight	450 grams (including three AA batteries)
Dimensions	H: 4.0", W: 2.8", D: 1.2"
Cable length	1.2 meters
Interface	Glenair quick disconnect (custom interface cables available separately)
Analog video rates	800 x 600 (SVGA 56 Hz to 85 Hz) 640 x 480 (VGA 60 Hz to 85 Hz)
Analog video inputs	R, G, B, HS Optional NTSC/RS-170 (A)
Controls	Brightness up/down Video flip
Power	Three AA batteries Operation >8 hrs
Alternative power	VIN 4.5-28 VDC, 1.5 W nominal

POWER OPERATED DISPLAY CONTROL MODULE

Mechanical	Clip on belt/reversible clip
Weight	380 grams
Dimensions	H: 4.0", W: 2.8", D: 1.2"
Cable length	1.6 meters
Interface	Glenair quick disconnect
Analog video rates	800 x 600 (SVGA 56 Hz to 85 Hz) 640 x 480 (VGA 60 Hz to 85 Hz)
Analog video inputs	NTSC/RS-170 (A), PAL, CVBS and Y/C S-VIDEO R, G, B, HS, S-VIDEO
Controls	RS-232
Power	VIN 6-24 VDC, 2.5 W nominal

ISO 9001:2000
Registered

AO CARD

Weight	~20grams
Dimensions	H: 2", W: 2.725", D: 0.063"
Analog video rates	800 x 600 (SVGA 56 Hz to 85 Hz)
Analog video inputs	R, G, B, HS Optional NTSC/RS-170 (A)
Controls	RS-232
Power	VIN 4.5-28 VDC, 1 W nominal

DESIGNED TO MEET THE FOLLOWING ENVIRONMENTAL PARAMETERS

Temperature	Operating: -32°C to +55°C
Storage	-32°C to +71°C
Humidity	Six 48-hour cycles, 20°C, 55°C, 95% RH
Salt fog	Four 24-hour cycles (two wet, two dry)
Vibration	Random vibration, 6 axis, 5 Hz to 2500 Hz, up to 40 gs
Immersion	Immersion in 1 meter of water for 2 hours

Glenair is a registered trademark of Glenair, Inc.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Building trust every day.

Rockwell Collins delivers smart communication and aviation electronic solutions to customers worldwide. Backed by a global network of service and support, we stand committed to putting technology and practical innovation to work for you whenever and wherever you need us. In this way, working together, we build trust. Every day.

For more information contact:

Rockwell Collins
2752 Loker Ave. West
Carlsbad, CA 92010
760.438.9255
Fax: 760.438.6875
E-mail: optronics@rockwellcollins.com
Web site: www.rockwellcollins.com/optronics

**Rockwell
Collins**

Building trust every day